

## STEAM HEATING

8mm O/D COPPER TUBE IS ATTACHED TO THE REAR GUARD TUBE IN A CONTINUOUS LOOP, FROM BOTTOM OF THE INDICATOR.

THE ENCLOSURE IS THEN FITTED AROUND THE INDICATOR TO PROTECT THE COPPER TUBE.

STEAM CAN BE FED THROUGH THE PIPE TO HEAT THE LIQUID IN THE PY-PASS TUBE.

## **EXAMPLE**

AMBIENT AIR TEMPERATURE = 20°C

STEAM PRESSURE 1.5 BAR = 68°C LIQUID TEMPERATURE STEAM PRESSURE 3 BAR = 85°C LIQUID TEMPERATURE

## NOTES:

- 1. MAXIMUM WORKING TEMPERATURE SHOULD NOT EXCEED 180°C
- 2. FOR TECHNICAL SPECIFICATIONS REFER TO G353218.

					1	1	COPPER T	JBE	8mm 0/D		
					ITEM No.	No. OFF	NAME	NAME		MATL OR PART No.	
	BKISTOL	COPYRIGHT IN THIS DRAWMO IS THE PROPERTY OF SETTU LIMITED © 2012. THE HFORMATION AND DESIGN CONTAINED HEREIN IS SETTU PROPERTY OF SECTION TO THE DESIGN HORTES OF SETTU LIMITED. THE DRAWMIG IS LENT WITHOUT CONSIDERATION OTHER THAN THE BORROWER'S AGREEMENT THAT IT IS NOT TO SE REPRODUCED. COPPED. THE HIPOMATION THEREOUT THE SETTU LIMITED. THE DESIGN HORTES OF THE LIMITED SETTING THE SETTING LIMITED. THE DESIGN HORTES OF THE LIMITED SETTING THE LIMITED SETING THE LIMITED SETTING THE L	THIRD ANGLE PROJECTION	DRAWN	JCF		RG. No.	No.		TITLE	MAGNETIC LIQUID
				DATE	09.02.	12	07574	277407			LEVEL INDICATOR STEAM HEATING
			CAD GENERATED DRAWING NO MANUAL REVISIONS ALLOWED	CHECKED	JIC		G353463			SEE PARTS LIST  FINISH  -	SEE PARTS LIST
				DATE	09.02.	12					
	BS1 6UT ENGLAND TEL: +44 (0) 117 927 9204	PARTIES, DIRECTLY OR INDIRECTLY, NOR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS SPECIFICALLY FURNISHED	ALL DIMENSIONS IN MILLIMETRES UNLESS STATED	SCALE	NTS	l i	LIMITS UNLESS STATED: DECIMAL PLACES (.X) ±0.25 WHOLE NUMBERS (X.) ±0.5				
	FAX: +44 (0) 117 929 8193 www.seetru.com	WITHOUT THE WRITTEN CONSENT OF SEETRU.	DO NOT SCALE DRAWING	ISSUE	1	- 1.	ANGLES ±0.5° CASTINGS ±0.8	.5*	U/0	_	

ENCLOSURE

STEEL